

HAND CRAFTED ZELLIGE

Authentic Zellige Tile



TECHNICAL SPECIFICATIONS	4" x 4"	2" x 6"	MOSAICS
Material Type	Zellige Terracotta	Zellige Terracotta	Zellige Terracotta
Finish	Glossy	Glossy	Glossy
Edge	Hand Cut	Hand Cut	Hand Cut
Color Variation	V3	V3	V3
Printing	N/A	N/A	N/A
Installation	Wall	Wall	Wall
Usage	Residential / Commercial	Residential / Commercial	Residential / Commercial
Grout Joint Recomm.	N/A	N/A	N/A
Thickness	3/8"	1.5 CM (15mm)	3/8"
Shower Pan	No	No	No
Pool Lining*	No	No	No
Fireplace Surround*	Yes	Yes	Yes
Frost Resistant	No	No	No

*Proper installation methods must be followed per project. Please reference TCNA for more information.

TEST RESULTS	4" x 4"	2" x 6"	MOSAICS
Water Absorption (C373)	N/A	N/A	N/A
Breaking Strength (C648)	N/A	N/A	N/A
Surface Abrasion (MOHS)	N/A	N/A	N/A
Chem. Resistance (C650)	Resistant	Resistant	Resistant
D.C.O.F. (A137.1)	N/A	N/A	N/A
Scratch Hardness (P.E.I)	N/A	N/A	N/A

- Special Considerations for Zellige Tile:
- Variation in caliber, flatness, straightness, texture, design and shade are present and inherent to the manufacture process of real zellige products.
 - Chips, pinholes and other imperfections are common in zellige tiles and are not defective. Material with these characteristics are not subject for exchange or return.
 - It is highly recommended to mix pieces from multiple cartons prior to installation in order to achieve a natural shade variation throughout the installation.
 - Zellige tiles look beautiful installed with or without grout, and with a variety of grout joint thicknesses. When installing in a wet area, grouting and sealing will be necessary.
 - Industry standard recommends overage by 15% in order to account for shortage due to tile cuts, breakage and future repairs.